

<b>PROPOSED INTERIOR WORKS FOR WORKS OF ARTIFICIAL TURF AND CIVIL WORKS FOR AIFF NATIONAL CENTER OF EXCELLENCE KOLKATA, WEST BENGAL, INDIA</b>					
<b>S.NO.</b>	<b>DESCRIPTION OF ITEM</b>	<b>UNIT</b>	<b>QTY.</b>	<b>RATE</b>	<b>AMOUNT</b>
	<b>GROUND FLOOR</b>				
<b>A</b>	<b>LOBBY AREA /MIX ZONE</b>				
<b>1</b>	<b>DOOR MAT - 2800 MM X 1375 MM</b>	Sqm	9.00		
	Providing & laying Trapper Matting (Heavy Duty) door mat of the approved				
	<b>MAKE - 3M/Euronics</b>				
<b>2</b>	<b>6MM THK BACK PAINTED GLASS</b>	Sqm	12.00		
	Providing and fixing 6mm Thk Back painted Glass (Saint Gobain Ultra Clear or equivalent) for writing board. BPG should be put over 12mm thk Ply Backing with all necessary beading and polish as per detail. All edges of glass to be machine				
<b>3</b>	<b>LAMINATE FINISH WALL PANELLING</b>	Sqm	7.00		
	Providing & fixing wall paneling with plywood of 12 mm thick. plywood and 1mm thick approved shade & quality laminate & teakwood beading where ever required on the plywood /hardwood				
<b>4</b>	<b>VINYL GRAPHICS</b>	Sqm	10.00		
	Supply & Installation of 3M Wall Décor Lite - Green ( NON-PVC), where in 48C20R will be used as a base material for printing and 8050M will be used as a Over laminate to protect the print from fading Graphics in matte finish with approved artwork digitally reproduced with water-based inks certified to have no hazardous air pollutants. Self-adhesive bubble-free installation to be done on a smooth, dust free putty surface that has a coat of oil-based primer. by Authorized				
<b>5</b>	<b>DOOR SIGNAGES</b>	no	6.00		
	Providing and installing General office signages made out of 6 mm thick acrylic sheet , with vinyl slider on top, as desired. Complete with adhesive/ 3M				
<b>6</b>	<b>PUSH AND PULL SIGNAGES</b>	no	6.00		
	Providing and fixing SS Finished Push/Pull Handles (set) of 150x150mm				

S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
<b>7</b>	<b>FIRE SIGNAGES</b>	LS	1.00		
	Providing & Fixing signages for Fire Exit Sign, Fire Evacuation Maps, MCP, Hooter				
<b>8</b>	<b>LAMINATE FINISH SKIRTING</b>	rmt	75.00		
	Providing & Fixing 12mm thk Ply with 1mm thk app. Shade of laminate Skirting with Rubber Gasket to hide the screws.				
<b>9</b>	<b>LOGO DESIGN</b>	LS	1.00		
	Providing & fixing 3D Letters made Logo in router cutting using 25 mm thick MDF board & finished in Duco paint as				
<b>B</b>	<b>CORRIDOR AREA</b>				
<b>1</b>	<b>VINYL GRAPHICS</b>	Sqm	20.00		
	Supply & Installation of 3M Wall Décor Lite - Green ( NON-PVC), where in 48C20R will be used as a base material for printing and 8050M will be used as a Over laminate to protect the print from fading Graphics in matte finish with approved artwork digitally reproduced with water-based inks certified to have no hazardous air pollutants. Self-adhesive bubble-free installation to be done on a smooth, dust free putty surface that has a coat of oil-based primer by Authorized				
<b>2</b>	<b>DOOR SIGNAGES</b>	no	8.00		
	Providing and installing General office signages made out of 6 mm thick acrylic sheet , with vinyl slider on top, as desired. Complete with adhesive/ 3M				
<b>3</b>	<b>PUSH AND PULL SIGNAGES</b>	no	8.00		
	Providing and fixing SS Finished Push/Pull Handles (set) of 150x150mm				
<b>4</b>	<b>FIRE SIGNAGES</b>	LS	2.00		
	Providing & Fixing signages for Fire Exit Sign, Fire Evacuation Maps, MCP, Hooter				
<b>C</b>	<b>TDR 1,2,5,6-LOCKER</b>				
<b>1</b>	<b>6MM THK BACK PAINTED GLASS</b>	Sqm	16.00		

S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
	Providing and fixing 6mm Thk Back painted Glass (Saint Gobain Ultra Clear or equivalent) for writing board. BPG should be put over 12mm thk Ply Backing with all necessary beading and polish as per detail. All edges of glass to be machine				
<b>2</b>	<b>LAMINATE FINISH WALL PANELLING</b>	Sqm	16.00		
	Providing & fixing wall paneling with plywood of 12 mm thick. plywood and 1mm thick approved shade & quality laminate & teakwood beading where ever required on the plywood /hardwood				
<b>3</b>	<b>PU PAINT FINISH DOOR PANELLING</b>	Sqm	30.00		
	P/A one or more coats of PU paint of approved make and color on Plastered surfaces, POP finished surfaces on False ceiling, slab soffit including appropriate surface preparation, to achieve a uniform				
<b>D</b>	<b>TDR 1,2,5,6-LOCKER TOILET</b>				
<b>1</b>	<b>WASH ROOM AREA MIRROR</b>	Sqm	20.00		
	Providing and fixing 12mm thk Marine ply with 6mm thk Mirror with polished edges with or without polished teakwood				
<b>E</b>	<b>TDR 3,4-LOCKER</b>				
<b>1</b>	<b>6MM THK BACK PAINTED GLASS</b>	Sqm	8.00		
	Providing and fixing 6mm Thk Back painted Glass (Saint Gobain Ultra Clear or equivalent) for writing board. BPG should be put over 12mm thk Ply Backing with all necessary beading and polish as per detail. All edges of glass to be machine				
<b>2</b>	<b>LAMINATE FINISH WALL PANELLING</b>	Sqm	8.00		
	Providing & fixing wall paneling with plywood of 12 mm thick. plywood and 1mm thick approved shade & quality laminate & teakwood beading where ever required on the plywood /hardwood				
<b>3</b>	<b>PU PAINT FINISH DOOR PANELLING</b>	Sqm	15.00		

S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
	P/A one or more coats of PU paint of approved make and color on Plastered surfaces, POP finished surfaces on False ceiling, slab soffit including appropriate surface preparation, to achieve a uniform				
<b>F</b>	<b>TDR 3 &amp; 4-LOCKER TOILET</b>				
<b>1</b>	<b>WASH ROOM AREA MIRROR</b>	Sqm	8.00		
	Providing and fixing 12mm thk Marine ply with 6mm thk Mirror with polished edges with or without polished teakwood				
<b>G</b>	<b>PHYSIO ROOM</b>				
<b>1</b>	<b>VINYL GRAPHICS</b>	Sqm	25.00		
	Supply & Installation of 3M Wall Décor Lite - Green ( NON-PVC), where in 48C20R will be used as a base material for printing and 8050M will be used as a Over laminate to protect the print from fading Graphics in matte finish with approved artwork digitally reproduced with water-based inks certified to have no hazardous air pollutants. Self-adhesive, bubble-free installation to be done on a smooth, dust free putty surface that has a coat of oil-based primer by Authorized				
<b>2</b>	<b>HANGING ROD WITH CURTAIN</b>	Sqm	2.00		
	Providing & fixing s.s rod with approved curtain as per site engineer. Rod will be fix to the wall and slab as per design.				
<b>3</b>	<b>SCREEN IN BASIN AREA</b>	Sqm	2.00		
	Providing and fixing 10mm thk Toughened glass screen with T.W. Frame 100 x 50mm thk as per design and detail. Wooden frame finished with Duco/Pu				
	<b>FIRST FLOOR</b>				
<b>A</b>	<b>TOILET AREA (MALE &amp; FEMALE)</b>				
<b>1</b>	<b>WASH ROOM AREA MIRROR</b>	Sqm	14.00		
	Providing and fixing 12mm thk Marine ply with 6mm thk Mirror with polished edges with or without polished teakwood				
<b>3</b>	<b>6MM THK BACK PAINTED GLASS IN</b>	Sqm	2.50		

S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
	Providing and fixing 6mm Thk Back painted Glass (Saint Gobain Ultra Clear or equivalent) for writing board. BPG should be put over 12mm thk Ply Backing with all necessary beading and polish as per detail. All edges of glass to be machine				
<b>B</b>	<b>CLASS ROOM</b>				
<b>1</b>	<b>ACOUSTIC SLIDING FOLDING</b>	Sqm	26.00		
	Providing & fixing extruded aluminum top track – for holding the partition panels; with necessary rectangular / flat sandwich plates as required, with special extruded aluminum profiles – on both ends; with stiffeners (horizontal) so as to form a rigid non-deflecting framework – duly fitted with extending rubber gaskets (seal) at the top & at the bottom level, filling the framework with fiber glass. Each framework will be fitted with a sheet of sound insulating material and finally laid				
	PANEL DESCRIPTION : 1) Panel Series: 100mm Thickness. 2) Acoustical Sound Rating: 50 DB (+-) 3) Panel Finish: Fabric / Laminate Finish as per design 4) Operation of Panel: Manual 5) Aluminum Trim Type: Standard, Exposed Trim in Natural 6) Seal Mechanism Type: Top & Bottom Retractable. 7) Stacking Arrangement: side Stacking				
<b>2</b>	<b>LAMINATE FINISH WALL PANELLING</b>	Sqm	35.00		
	Providing & fixing wall paneling with plywood of 12 mm thick. plywood and 1mm thick approved shade & quality laminate & teakwood beading where ever required on the plywood /hardwood				
<b>3</b>	<b>MOTORISED PROJECTION SCREEN-</b>	No	2.00		

S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
	<p>Providing and fixing projection screen conforming to the following size &amp; specifications:            Size = 2030mm x 1530mm            Projection system : Orthographic projection            Appearance sharps: Square (quadrilateral)            Material of screen surface: Matte white            Controls : Power switch, Wireless remote control (Equipped with three buttons : up, stop, down)            Plug Power : Arbitrary national standard plugs, 110V—127V / 220V—240V            Motor: Synchronous motor, Tubular</p>				
<b>4</b>	<b>ROLLER BLINDS - 5% POROSITY</b>	Sqm	45.00		
	<p>Roller Blinds with 5% openness factor. Supply &amp; Installation of manually operated roller Blinds.HARDWARE; TOP TUBE : Made of extruded aluminium with 38 mm Dia. and wall thickness of 1.2 mm with spline adoptable to accommodate clutch. CLUTCH MECHANISM : Moulded plastic having self lubrication with Glass fibre reinforcement, having a minimum lifting capacity of 8 lbs weight capacity - 8 lbs Head adoptability - 38 mm OPERATING CHAIN : PLASTIC ball chain adoptable to the clutch pitch for smooth operation of blinds. LOCKING MEMBER : Plastic/ steel stop locks for limit setting adoptable to the steel chain.Bonding ( Fabric &gt; Tube ) : 30/36 mm wide double sided adhesive tape of 3M for strong holding capacity. SPRING BOOSTERS: provided as per the requirement Bottom Bar : aluminium extruded circular section with powder coated finish, having a Min. weight to be 365 gms / Rmt for a perfect fall of fabric to avoid warpage / floating. Ends are covered with end caps to give a perfect finish. FABRIC: - Screen fabric. Composition: 30% polyester and 70% PVC.Openness factor - 5%, Weight 380 gms / sq mtr +/- 5%, thickness 0.53 mm</p>				
<b>5</b>	<b>TRANSITION Z PROFILE</b>	Rmt	45.00		
	<p>Providing &amp; fixing SS Finished Transition "Z" profile for the seamless joints between Carpet/Vinyl &amp; other types of</p>				
<b>C</b>	<b>OFFICE AREA</b>				

S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
1	<b>6MM THK BACK PAINTED GLASS</b>	Sqm	20.00		
	Providing and fixing 6mm Thk Back painted Glass (Saint Gobain Ultra Clear or equivalent) for writing board. BPG should be put over 12mm thk Ply Backing with all necessary beading and polish as per detail. All edges of glass to be machine				
2	<b>LAMINATE FINISH WALL PANELLING</b>	Sqm	14.00		
	Providing & fixing wall paneling with plywood of 12 mm thick. plywood and 1mm thick approved shade & quality laminate & teakwood beading where ever required on the plywood /hardwood				
3	<b>SOFT BOARD PANELING</b>	Sqm	12.00		
	Providing and fixing Fabric wrapped soft board panels 12mm thick of size and profile as per detail with 12mm grooves made at the junction of soft board and partition with edges finished in PVC wall gripper. Soft board to be fixed on a backing of 6mm commercial ply. The rate should include cladding the panels in approved fabric (Basic Rate of Fabric Rs.120/Bmt). Note the fabric shall be				
4	<b>ROLLER BLINDS - 5% POROSITY</b>	Sqm	45.00		

S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
	Roller Blinds with 5% openness factor:- Supply & Installation of manually operated roller Blinds.HARDWARE; TOP TUBE : Made of extruded aluminium with 38 mm Dia. and wall thickness of 1.2 mm with spline adoptable to accommodate clutch. CLUTCH MECHANISM : Moulded plastic having self lubrication with Glass fibre reinforcement, having a minimum lifting capacity of 8 lbs weight capacity - 8 lbs Head adoptability - 38 mm OPERATING CHAIN : PLASTIC ball chain adoptable to the clutch pitch for smooth operation of blinds. LOCKING MEMBER : Plastic/ steel stop locks for limit setting adoptable to the steel chain.Bonding ( Fabric > Tube ) : 30/36 mm wide double sided adhesive tape of 3M for strong holding capacity. SPRING BOOSTERS: provided as per the requirement Bottom Bar : aluminium extruded circular section with powder coated finish, having a Min. weight to be 365 gms / Rmt for a perfect fall of fabric to avoid warpage / floating. Ends are covered with end caps to give a perfect finish. FABRIC: - Screen fabric. Composition: 30% polyester and 70% PVC.Openness factor - 5%, Weight 380 gms / sq mtr +/- 5%, thickness 0.53 mm				
<b>5</b>	<b>TRANSITION Z PROFILE</b>				
	Providing & fixing SS Finished Transition "Z" profile for the seamless joints between Carpet/Vinyl & other types of	Rmt	45.00		
<b>D</b>	<b>MEETING ROOM</b>				
<b>1</b>	<b>6MM THK BACK PAINTED GLASS</b>	Sqm	28.00		
	Providing and fixing 6mm Thk Back painted Glass (Saint Gobain Ultra Clear or equivalent) for writing board. BPG should be put over 12mm thk Ply Backing with all necessary beading and polish as per detail. All edges of glass to be machine				
<b>2</b>	<b>LAMINATE FINISH WALL PANELLING</b>	Sqm	6.00		



S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
	Providing & fixing wall paneling with plywood of 12 mm thick. plywood and 1mm thick approved shade & quality laminate & teakwood beading where ever required on the plywood /hardwood				
<b>3</b>	<b>VINYL GRAPHICS</b>	Sqm	24.00		
	Supply & Installation of 3M Wall Décor Lite - Green ( NON-PVC), where in 48C20R will be used as a base material for printing and 8050M will be used as a Over laminate to protect the print from fading Graphics in matte finish with approved artwork digitally reproduced with water-based inks certified to have no hazardous air pollutants. Self-adhesive bubble-free installation to be done on a smooth, dust free putty surface that has a coat of oil-based primer. by Authorized				
<b>4</b>	<b>LAMINATE FINISH LEDGE SEATING</b>	Sqm	12.00		
	Providing and fixing Seating as per design and detail. top made of 18mm thk ply with 1mm thk Laminate finish top as per detail. Base of table made of 18 mm thk play with 1 mm thk laminate				
<b>5</b>	<b>ACOUSTIC PANELING</b>	Sqm	9.00		
	Providing / fixing of ECO ACOUSTICS PANELS of 12mm thickness of selected colour above the flat wall / partition surface with suitable adhesive/3M double				
<b>6</b>	<b>WALL PAPER WORK</b>	Sqm	28.00		

S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
	<b>Wall paper</b> : Provide & install of wallcovering PVC coated with woven cotton or woven polyester backing with a grammage of 350 to 450 Gms/Sqm. The substratum/base shall be flat POP/Gypboard surface. Pre-treat the substrate with primer with a block brush or Spray and allow it to dry for minimum 8 hours the substrate base moisture level should not exceed 6% of the building moisture limit (to be verified with hygrometer). the temperature of the underlying surface must be at least 10 degree. The wallcovering shall be devoid of toxic metals and shall incorporate fire retardant and antimicrobial property. Wallcovering to be applied to this base with fixing adhesive containing fungicides with on rubbery odour and noninflammable property (no solvents) as				
<b>E</b>	<b>TECHNICAL ROOM</b>				
<b>1</b>	<b>LAMINATE FINISH WALL PANELLING</b>	Sqm	6.00		
	<b>Vinyl Flooring:</b> P/I of flexible homogeneous, calendered compacted vinyl flooring, suitable for heavy traffic area, of thickness 2mm and with PUR surface treatment and group P wear				
<b>2</b>	<b>SOFT BOARD PANELING</b>	Sqm	2.00		
	Providing and fixing Fabric wrapped soft board panels 12mm thick of size and profile as per detail with 12mm grooves made at the junction of soft board and partition with edges finished in PVC wall gripper. Soft board to be fixed on a backing of 6mm commercial ply. The rate should include cladding the panels in approved fabric (Basic Rate of Fabric Rs.120/Rmt). Note the fabric shall be				
<b>3</b>	<b>ROLLER BLINDS - 5% POROSITY</b>	Sqm	20.00		

S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
	Roller Blinds with 5% openness factor: Supply & Installation of manually operated roller Blinds.HARDWARE; TOP TUBE : Made of extruded aluminium with 38 mm Dia. and wall thickness of 1.2 mm with spline adoptable to accommodate clutch. CLUTCH MECHANISM : Moulded plastic having self lubrication with Glass fibre reinforcement, having a minimum lifting capacity of 8 lbs weight capacity - 8 lbs Head adoptability - 38 mm OPERATING CHAIN : PLASTIC ball chain adoptable to the clutch pitch for smooth operation of blinds. LOCKING MEMBER : Plastic/ steel stop locks for limit setting adoptable to the steel chain.Bonding ( Fabric > Tube ) : 30/36 mm wide double sided adhesive tape of 3M for strong holding capacity. SPRING BOOSTERS: provided as per the requirement Bottom Bar : aluminium extruded circular section with powder coated finish, having a Min. weight to be 365 gms / Rmt for a perfect fall of fabric to avoid warpage / floating. Ends are covered with end caps to give a perfect finish. FABRIC: - Screen fabric. Composition: 30% polyester and 70% PVC.Openness factor - 5%, Weight 380 gms / sq mtr +/- 5%, thickness 0.53 mm				
<b>F</b>	<b>CABIN AREA</b>				
<b>1</b>	<b>LAMINATE FINISH WALL &amp; DOOR</b>	Sqm	9.00		
	Providing & fixing wall paneling with plywood of 12 mm thick. plywood and 1mm thick approved shade & quality laminate & teakwood beading where ever required on the plywood /hardwood				
<b>2</b>	<b>SOFT BOARD PANELING</b>	Sqm	1.00		
	Providing and fixing Fabric wrapped soft board panels 12mm thick of size and profile as per detail with 12mm grooves made at the junction of soft board and partition with edges finished in PVC wall gripper. Soft board to be fixed on a backing of 6mm commercial ply. The rate should include cladding the panels in approved fabric (Basic Rate of Fabric Rs.120/Rmt). Note the fabric shall be				

S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
<b>3</b>	<b>CABIN LAMINATE FINISH LEDGE</b>	Sqm	5.00		
	Providing and fixing LEDGE as per design and detail. Ledge top made of 18mm thk ply with 1mm thk Laminate finish top as per detail. Front and back made of 12				
<b>4</b>	<b>ROLLER BLINDS - 5% POROSITY</b>	Sqm	25.00		
	Roller Blinds with 5% openness factor: Supply & Installation of manually operated roller Blinds.HARDWARE; TOP TUBE : Made of extruded aluminium with 38 mm Dia. and wall thickness of 1.2 mm with spline adoptable to accommodate clutch. CLUTCH MECHANISM : Moulded plastic having self lubrication with Glass fibre reinforcement, having a minimum lifting capacity of 8 lbs weight capacity - 8 lbs Head adoptability - 38 mm OPERATING CHAIN : PLASTIC ball chain adoptable to the clutch pitch for smooth operation of blinds. LOCKING MEMBER : Plastic/ steel stop locks for limit setting adoptable to the steel chain.Bonding ( Fabric > Tube ) : 30/36 mm wide double sided adhesive tape of 3M for strong holding capacity. SPRING BOOSTERS: provided as per the requirement Bottom Bar : aluminium extruded circular section with powder coated finish, having a Min. weight to be 365 gms / Rmt for a perfect fall of fabric to avoid warpage / floating. Ends are covered with end caps to give a perfect finish. FABRIC: - Screen fabric. Composition: 30% polyester and 70% PVC.Openness factor - 5%, Weight 380 gms / sq mtr +/- 5%, thickness 0.53 mm				
<b>G</b>	<b>CONFERENCE ROOM</b>				
<b>1</b>	<b>LAMINATE FINISH WALL PANELLING</b>	Sqm	6.00		
	Providing & fixing wall paneling with plywood of 12 mm thick. plywood and 1mm thick approved shade & quality laminate & teakwood beading where ever required on the plywood /hardwood				
<b>2</b>	<b>SOFT BOARD PANELING</b>	Sqm	2.00		

S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
	Providing and fixing Fabric wrapped soft board panels 12mm thick of size and profile as per detail with 12mm grooves made at the junction of soft board and partition with edges finished in PVC wall gripper. Soft board to be fixed on a backing of 6mm commercial ply. The rate should include cladding the panels in approved fabric (Basic Rate of Fabric Rs.120/Rmt). Note the fabric shall be				
<b>3</b>	<b>ROLLER BLINDS - 5% POROSITY</b>	Sqm	5.00		
	Roller Blinds with 5% openness factor. Supply & Installation of manually operated roller Blinds.HARDWARE; TOP TUBE : Made of extruded aluminium with 38 mm Dia. and wall thickness of 1.2 mm with spline adoptable to accommodate clutch. CLUTCH MECHANISM : Moulded plastic having self lubrication with Glass fibre reinforcement, having a minimum lifting capacity of 8 lbs weight capacity - 8 lbs Head adoptability - 38 mm OPERATING CHAIN : PLASTIC ball chain adoptable to the clutch pitch for smooth operation of blinds. LOCKING MEMBER : Plastic/ steel stop locks for limit setting adoptable to the steel chain.Bonding ( Fabric > Tube ) : 30/36 mm wide double sided adhesive tape of 3M for strong holding capacity. SPRING BOOSTERS: provided as per the requirement Bottom Bar : aluminium extruded circular section with powder coated finish, having a Min. weight to be 365 gms / Rmt for a perfect fall of fabric to avoid warpage / floating. Ends are covered with end caps to give a perfect finish. FABRIC: - Screen fabric. Composition: 30% polyester and 70% PVC.Openness factor - 5%, Weight 380 gms / sq mtr +/- 5%, thickness 0.53 mm				
<b>4</b>	<b>TV UNIT</b>	Sqm	1.00		
	Providing & fixing wall TV Unit with plywood of 18 mm thick. plywood and 1mm thick approved shade & quality laminate & teakwood beading where				
<b>5</b>	<b>LAMINATE FINISHED TABLE (5.9 X</b>	no	1.00		

S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
	Providing and fixing Table as per design and detail. Table top made of 18mm thk marine ply with App. 1mm thk Laminate finish from out and inside as per detail. Base of the table made of 18 mm thk				
<b>H</b>	<b>REFRESHMENT AREA</b>				
<b>1</b>	<b>6MM THK BACK PAINTED GLASS</b>	Sqm	15.00		
	Providing and fixing 6mm Thk Back painted Glass (Saint Gobain Ultra Clear or equivalent) for writing board. BPG should be put over 12mm thk Ply Backing with all necessary beading and polish as per detail. All edges of glass to be machine				
<b>2</b>	<b>LAMINATE FINISH BOX PANELLING</b>	Sqm	30.00		
	Providing & fixing wall BOXING with plywood of 18 mm thick. plywood and 1mm thick approved shade & quality laminate & teakwood beading where				
<b>3</b>	<b>ROLLER BLINDS - 5% POROSITY</b>	Sqm	45.00		

S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
	Roller Blinds with 5% openness factor: Supply & Installation of manually operated roller Blinds.HARDWARE; TOP TUBE : Made of extruded aluminium with 38 mm Dia. and wall thickness of 1.2 mm with spline adoptable to accommodate clutch. CLUTCH MECHANISM : Moulded plastic having self lubrication with Glass fibre reinforcement, having a minimum lifting capacity of 8 lbs weight capacity - 8 lbs Head adoptability - 38 mm OPERATING CHAIN : PLASTIC ball chain adoptable to the clutch pitch for smooth operation of blinds. LOCKING MEMBER : Plastic/ steel stop locks for limit setting adoptable to the steel chain.Bonding ( Fabric > Tube ) : 30/36 mm wide double sided adhesive tape of 3M for strong holding capacity. SPRING BOOSTERS: provided as per the requirement Bottom Bar : aluminium extruded circular section with powder coated finish, having a Min. weight to be 365 gms / Rmt for a perfect fall of fabric to avoid warpage / floating. Ends are covered with end caps to give a perfect finish. FABRIC: - Screen fabric. Composition: 30% polyester and 70% PVC.Openness factor - 5%, Weight 380 gms / sq mtr +/- 5%, thickness 0.53 mm				
<b>J</b>	<b>OUT SIDE TERRACE AREA</b>				
<b>1</b>	<b>TERRACE OPEN AREA ROOFING</b>				
	P/F M.Sf Structural Section capable of carrying and uniformly distributing a dead load as per given drawing. The construction will consist of fabricated post placed at a distance as per detail drawing. These support legs will be made out of MS ISMA sections welded together to form a box section with 12 thk 300 x 300 MS plate welded to this box section at bottom . The bottom plate will be anchored to the RCC base slab with	Sqm	####		
<b>L</b>	<b>MISCELLANEOUS WORK</b>				
<b>1</b>	<b>FROSTED FILM</b>	Sqm	####		

S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
	Providing and fixing frosted crystal film over the glass partition/door as per the design. The film should be Electronically /computer plotter cut and applied on glass and other rigid, clear substrates in pattern as per drawings including design.				
<b>2</b>	<b>DOOR SIGNAGES</b>	no	26.00		
	Providing and installing General office signages made out of 6 mm thick acrylic sheet , with vinyl slider on top, as desired. Complete with adhesive/ 3M				
<b>3</b>	<b>PUSH AND PULL SIGNAGES</b>	no	26.00		
	Providing and fixing SS Finished Push/Pull Handles (set) of 150x150mm				
<b>4</b>	<b>FIRE SIGNAGES</b>	LS	1.00		
	Providing & Fixing signages for Fire Exit Sign, Fire Evacuation Maps, MCP, Hooter				
<b>5</b>	<b>DOOR MAT - 900 MM X 600 MM</b>	Sqm	5.00		
	Providing & laying Trapper Matting (Heavy Duty) door mat of the approved <b>MAKE-3M/Euronics</b>				
<b>6</b>	<b>TRAP DOOR IN CEILING</b>	Sqm	2.00		
	Providing and fixing trape door in ceiling with 18mm thk ply with 1mm thk laminate finish. All the edges should be finish with 3mm beading with polish.				
<b>7</b>	<b>WINDOW PELMET -PAINT FINISHED</b>	RMT	90.00		
	Providing and fixing 18 mm thick plywood faced with 12MM Thk Gypsum on top finish with paint as per approved shade for pelmet box on visible surface				
	<b>FURNITURE</b>				
	<b>GROUND FLOOR</b>				
<b>1</b>	<b>RECEPTION AREA</b>				
a	Reception Chair Features: Mid Back with Upholstered Seat & Mesh Back, Knee Tilt KT Mechanism, Adjustable Armrest, Gaslift for Seat height adjustment, Standard 5-prong Nylon	no	1.00		



S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
b	SINGLE SEATER SOFA Top: Fabric/PU Understructure:Base With SS metal Frame Legs with Matt Finish	no	6.00		
C	CENTER TABLE ( 600 DIA) Features: Top: Glass Top - 12mm toughned glass with rounded edges.	no	3.00		
d	<b>DUCO FINISHED RECEPTION TABLE</b> Providing and constructing Reception Table of size 2600 x 750 mm in two tier with table top in 19 mm thick commercial ply/mdf finished with approved Duco Paint, 1.0 mm thick Laminate on second tier, with 2 mm thick PVC edge binding on the edges. The internal portion to be in laminate. Supports to be in ply boxing finished in laminate. The rate to include credenza of size 1000x450x750mm with top, sides and intermediate in 19 mm ply finished in matching laminate on the under side and approved 1.0mm thk Laminate in all exposed sides. Shutters to be in 19mm	no	1.00		
<b>2</b>	<b>TDR 3 &amp; 4 MASSAGE ROOM</b>				
a	Massage table Massage table Providing & fixing Massage Table as per the design and details, table top made of 18mm thk Marine Ply with 1.0mm thk laminate on both sides as per the details. The framework of the table shall be made of Plywood/Teak wood as per the details duly polished/duco painted. Edges of the table to be lipped with Teak Wood.	no	4.00		
<b>3</b>	<b>PHYSIO ROOM</b>				
a	Massage table Massage table Providing & fixing Massage Table as per the design and details, table top made of 18mm thk Marine Ply with 1.0mm thk laminate on both sides as per the details. The framework of the table shall be made of Plywood/Teak wood as per the details duly polished/duco painted. Edges of the table to be lipped with Teak Wood.	no	4.00		
b	Working Table – 1800 X 750MM	no	1.00		

S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
	Free standing table :- Top made of 25mm thick parelam partical board with 2mm thk PVC edge Banding all approx top Size- 1800mm Wx 750D. Top Supported on 18mm thk prelam leg & exposed edge finished with PVC edge banding. 700mm leg height. Other-				
C	Chair (Mid Back- Basic Rate-6500)	no	2.00		
	Chair (Mid Back Features: Mid Back with Upholstered Seat & Mesh Back, Knee Tilt KT Mechanism, Adjustable Armrest, Gaslift for Seat height adjustment, Standard 5-prong Nylon				
	<b>FIRST FLOOR</b>				
<b>1</b>	<b>CLASS ROOM 1 &amp; 2</b>				
a	Tablet chair Providing & fixing of Class Room Chairs with PP Arms & Back, Folding Writing Pad, Pipe stand, Fabric Tapestry, etc	no	60.00		
b	Movable desk Providing & Constructing Movable Desk of size 1200 x 600 mm with table top in 19 mm thick Prelam particle board finished in approved colour and shade and balancing laminate on the under side, with heavy duty PVC edge binding,	no	2.00		
C	Podium Providing & fixing 1500mm High & 600mm wide Podium made out of 18mm thk Plywood finished with 1.0mm thk Laminate on both side with PVC Edge bending/woodn lipping with polish	no	2.00		
d	Chair (Mid Back Features: Mid Back with Upholstered Seat & Mesh Back, Knee Tilt KT Mechanism, Adjustable Armrest, Gaslift for Seat height adjustment, Standard 5-prong Nylon	no	2.00		
<b>2</b>	<b>OFFICE SPACE</b>				
a	<b>Triangle Shape work station</b>	no	18.00		

S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
	Top made of 25mm thick prelam partical board with 2mm thk PVC edge Banding all approx top Size- 1200mm Wx 600D. Top Supported on 18mm thk prelam leg & exposed edge finished with PVC edge banding. Providing half pedestal ( 3Drawer) locking arrangement 'C' Hnadle. Size of combo storage-700 X 400mmWx450mmD. Other Room				
b	<b>Linear Work Station- 1200 x 600MM</b>	no	2.00		
	52mm thick partition panel 1200mm height. ICP & BCP fix below table top. Above the table top Full laminate writingboard. Table top- worktop of 25mm thick prelam partical board with 2mm thick PVC hot pressed edge bending all across the worktop ( size - 1200mmW x 600mmD ) <b>Gable end-</b> 25mm thk galbe end made out of prelaminated partical board. all edge finish with 2mm thk PVC edge binding. 700mm height of the leg. <b>Pedestal</b> The top rest pedestal unit shall have oter dimension of 700mm H x 400mm W x 450mm D. the drawer unit shall consist of				
C	Chair (Mid Back Features: Mid Back with Upholstered Seat & Mesh Back, Knee Tilt KT Mechanism, Adjustable Armrest, Gaslift for Seat height adjustment, Standard 5-prong Nylon	no	22.00		
d	SINGLE SEATER SOFA Top: Fabric/PU Understructure:Base With SS metal Frame Legs with Matt Finish	no	2.00		
e	CENTER TABLE ( 600 DIA) Features: Top: Glass Top - 12mm toughned glass with rounded edges	no	1.00		
<b>3</b>	<b>MEETING ROOM 1 &amp; 2</b>				
a	Three seater round sofa Top: Fabric/PU finished with 35mm thk pu foam	no	1.00		
b	Single seater sofa chair Fabric Upholstered seat & back with injection shaping PU foam on mild steel	no	2.00		
C	Center Table (900 DIA) Table with BSL top of 25mm thk with all Side Edgebanding suported by MS Bracket duly powder coated. Center pipe	no	1.00		

S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
d	Pouf seating Wooden frame with high density foam covered with upholstrey of leatherite/Fabric SS Legs at bottom.	no	4.00		
<b>4</b>	<b>TECHNICAL ROOM</b>				
<b>a</b>	<b>Linear Work Station- 1350 x 750MM</b>	no	6.00		
	Free standing table :- Top made of 25mm thick parelam partical board with 2mm thk PVC edge Banding all approx top Size- 1350mm Wx 750D. Top Supported on 18mm thk prelam leg & exposed edge finished with PVC edge banding. 700mm leg height. Other-				
<b>b</b>	<b>Modular Storage -1350 x 900MM X</b>	no	2.00		
	Providing & fixing file full height storage made out of prelaminated partical board , back & shutters in 18mm thk prelaminated partical board. Clad with 1mm thk laminate from outside & 1mm Laminate from inside. all the edges finish				
<b>C</b>	SINGLE SEATER SOFA Top: Fabric/PU Understructure:Base With SS metal Frame Legs with Matt Finish	no	2.00		
<b>d</b>	CENTER TABLE ( 600 DIA) Features: Top: Glass Top - 12mm toughned glass with rounded edges.	no	1.00		
<b>e</b>	Chair (Mid Back Features: Mid Back with Upholstered Seat & Mesh Back, Knee Tilt KT Mechanism, Adjustable Armrest, Gaslift for Seat height adjustment, Standard 5-prong Nylon	no	6.00		
<b>5</b>	<b>CABIN AREA</b>				
<b>a</b>	Working Table – 2100 X 900MM	no	1.00		

S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
	Free standing table :- Top made of 25mm thick parelam partical board with 2mm thk PVC edge Banding all approx top Size- 2100mm Wx 900D. Top Supported on 18mm thk prelam leg & exposed edge finished with PVC edge banding. 700mm leg height. 18mm thick prelam modesty 525mm H. Size- 1500mmWx525mmH. Side credenza combo- 25mm thk top made out of prelaminated partical board. all edge finished with 2mm thk PVC edge banding. Entire body made out of 18mm thk prelaminated partical board.Providing half pedestal ( 1Drawer + 1HDU shutter )				
<b>b</b>	Three seater sofa Top: Fabric/PU finished with 35mm thk pu foam	no	1.00		
<b>C</b>	SINGLE SEATER SOFA Top: Fabric/PU Understructure:Base With SS metal Frame Legs with Matt Finish	no	2.00		
<b>d</b>	Center Table- 900 x 600MM Features: Top: Glass Top - 12mm toughned glass with rounded edges	no	1.00		
<b>e</b>	Side Table-600 x 600MM Features: Top: Glass Top - 12mm toughned glass with rounded edges	no	2.00		
<b>f</b>	Chair (High Back- Basic Rate-12000) Features: High Back, Mesh Back, Cushion Headrest & Silver Epoxy Backbone, Synchronized Mechanism, Adjustable Armrest, Gaslift for Seat height	no	1.00		
<b>g</b>	Chair (Mid Back- Basic Rate-10500) Features: Mid Back, Mesh Back & Silver Epoxy Backbone, Synchronized Mechanism, Adjustable Armrest, Gaslift	no	3.00		
<b>6</b>	<b>CONFERENCE ROOM</b>				
<b>a</b>	Chair (Mid Back- Basic Rate-10500) Features: Mid Back, Mesh Back & Silver Epoxy Backbone, Synchronized Mechanism, Adjustable Armrest, Gaslift	no	20.00		
<b>7</b>	<b>REFRESHMENT AREA</b>				

S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
a	Dining Table- 1000 x 1000MM Providing & Constructing Dining table of size 1000 x 1000 mm with table top in 19 mm thick commercial ply finished in approved colour and shade 19 mm thick granite on the top and balancing laminate on the under side, edge	no	4.00		
b	Dining Chair Providing & Supplying of Stackable Dining Chairs with heavy duty PP Seat &	no	16.00		
C	Bar Stool Providing & supplying 450mm dia Bar Stool made of 35mm thk pu foam finished with Pu/Fabric upholstery having	no	11.00		
d	Three seater sofa Top: Fabric/PU finished with 35mm thk pu foam	no	2.00		
e	SINGLE SEATER SOFA Top: Fabric/PU Understructure:Base With SS metal Frame Legs with Matt Finish	no	4.00		
f	Center Table- 900 x 600MM Features: Top: Glass Top - 12mm toughned glass with rounded edges	no	2.00		
g	Side Table-600 x 600MM Features: Top: Glass Top - 12mm toughned glass with rounded edges	no	4.00		
<b>8</b>	<b>CONNECTING TERRACE AREA</b>				
a	Dining Table- 1000 x 1000MM Providing & Constructing Dining table of size 1000 x 1000 mm with table top in 19 mm thick commercial ply finished in approved colour and shade 19 mm thick granite on the top and balancing laminate on the under side, edge	no	6.00		
b	Dining Chair Providing & Supplying of Stackable Dining Chairs with heavy duty PP Seat &	no	24.00		
C	Two seater sofa Top: Fabric/PU finished with 35mm thk pu foam	no	4.00		
d	SINGLE SEATER SOFA Top: Fabric/PU Understructure:Base With SS metal Frame Legs with Matt Finish	no	4.00		

S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
e	Center Table- 900 x 600MM Features: Top: Glass Top - 12mm toughned glass with rounded edges.	no	2.00		
	<b>Ground Floor</b>				
	<b>TDR 1,2,5,6-LOCKER</b>				
1	<b>TDR- LOCKER 750MM X 750MM</b>	NO	80.00		
	Metal lockers Fabricated with 1mm thck CRCA sheet and MS powder coating finish with Pvc depressed handle and Normal lock 750mm (W) x 450mm (D) x 750mm (H) Locker body carcass in 1mm thick CRCA sheet. Shutters in 1mm thick CRCA sheet. Ø5 mm perforations on shutter for air circulation. Metal Concealed handle Normal lock is considered Soft closing hinges for shutter. Powder coating thickness 60-80 microns. M8x20mm adjustable leveller bolts				
2	<b>TDR- LOCKER BENCH-2400 X 450MM</b>	NO	12.00		
	Providing and fixing Locker Bench as per design and detail. Table top made of 18mm thk ply with 1mm thk Laminate finish top as per detail. Base of table				
3	<b>600 DEEP STORAGE</b>	Sqm	26.00		
	Providing & fixing full height / half height storage made out of 18 mm thk plywood for box ,6mm ply wood back & shutters in 18mm thk Plywood. Clad with 1mm thk laminate from outside & 1mm				
	<b>TDR 3,4-LOCKER</b>				
1	<b>TDR- LOCKER 750MM X 750MM</b>	NO	50.00		
	Providing and fixing Locker Table and storage as per design and detail. Table top made of 18mm thk ply with 1mm thk Laminate finish top as per detail. Base of table made of 18 mm thk play with 1 mm thk laminate. Overhead storage				
2	<b>TDR- LOCKER BENCH-2400 X 450MM</b>	NO	6.00		

S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
	Providing and fixing Locker Bench as per design and detail. Table top made of 18mm thk ply with 1mm thk Laminate finish top as per detail. Base of table				
<b>3</b>	<b>600 DEEP STORAGE</b>	Sqm	12.00		
	Providing & fixing full height / half height storage made out of 18 mm thk plywood for box ,6mm ply wood back & shutters in 18mm thk Plywood. Clad with 1mm thk laminate from outside & 1mm				
<b>PHYSIO ROOM</b>					
<b>1</b>	<b>450 DEEP STORAGE</b>	Sqm	12.00		
	Providing & fixing full height / half height storage made out of 18 mm thk plywood for box ,6mm ply wood back & shutters in 18mm thk Plywood. Clad with 1mm thk laminate from outside & 1mm				
<b>First Floor</b>					
<b>TOILET AREA (MALE &amp; FEMALE)</b>					
<b>1</b>	<b>450 DEEP STORAGE</b>	Sqm	14.00		
	Providing & fixing full height / half height storage made out of 18 mm thk plywood for box ,6mm ply wood back & shutters in 18mm thk Plywood. Clad with 1mm thk laminate from outside & 1mm				
<b>OFFICE AREA</b>					
<b>1</b>	<b>450 DEEP STORAGE</b>	Sqm	8.00		
	Providing & fixing full height / half height storage made out of 18 mm thk plywood for box ,6mm ply wood back & shutters in 18mm thk Plywood. Clad with 1mm thk laminate from outside & 1mm				
<b>TECHNICAL ROOM</b>					
<b>1</b>	<b>450 DEEP STORAGE</b>	Sqm	3.00		
	Providing & fixing full height / half height storage made out of 18 mm thk plywood for box ,6mm ply wood back & shutters in 18mm thk Plywood. Clad with 1mm thk laminate from outside & 1mm				
<b>CABIN AREA</b>					
<b>1</b>	<b>450 DEEP STORAGE</b>	Sqm	10.00		



S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
	Providing & fixing full height / half height storage made out of 18 mm thk plywood for box ,6mm ply wood back & shutters in 18mm thk Plywood. Clad with 1mm thk laminate from outside & 1mm				
	<b>REFRESHMENT AREA</b>				
<b>1</b>	<b>600 DEEP COUNTER STORAGE</b>	Sqm	8.00		
	Providing & fixing full height / half height storage made out of 18 mm thk plywood for box ,6mm ply wood back & shutters in 18mm thk Plywood. Clad with 1mm thk laminate from outside & 1mm				
<b>1</b>	<b>300 DEEP OVERHEAD STORAGE</b>	Sqm	8.00		
	Providing & fixing Overhead storage made out of 18 mm thk. plywood for box ,6mm ply wood back & shutters in 18mm thk Plywood. Clad with 1mm thk laminate from outside & 1mm Laminate				
	<b>SANITARY WORKS:</b>				
<b>1</b>	Supply, installation, testing and commissioning of white colour vitreous china single trap symphonic pattern having back inlet, supporting chair, wall hung water closet with concealed cistern and CP brass flush bend (European type) with seat and lid "Thermoset moulded (bakelite) IS 2548 Part I, with C.P. brass hinges and rubber buffers, adapter, rubber joints fixed to W.C., C.P. brass screwed washers including cutting and	no	5.00		
	EWC - Hindware Model Dove-20080 Concealed Cistern Model-508179 - with conc. cistern front actuation dual flush, gloss actuator plate, EWC flexible				

S.NO.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
2	Supply, installation, testing and commissioning vitreous china flat back large urinal with concealed wall hangers, fully automatic photoelectric cell operated No-touch urinal flushing system (Electrical operated vandal proof-twin flush (pre & post use) operation), flush mounted sensors complete in all respects in fully operational conditions, C.P. brass flush pipe with C.P. clamps and screws, C.P. flange with spreader, 32 mm C.P. cast brass bottle trap and pipe.	no	8.00		
3	Supply, installation, testing & commissioning wash basin with CP waste coupling of standard pattern, 32 mm dia C.P. cast brass bottle tarp & union, 32 mm dia C.P. pipe to wall and C.P. wall flange, complete including cutting and making good the walls where required.(Make : Hindware, Model : Garnet, Cat NO.10080, pillar cock, Model:	no	3.00		
4	Supply, installation, testing and commissioning ablution spray unit comprising of CP flexible hose, spray, wall	no	5.00		
5	Supply, installation, testing and commissioning 15 mm C.P. angle valves with polypropylene filter, union, nut and C.P. cast brass wall flange complete	no	8.00		
6	Supply, installation, testing and commissioning toilet paper holding including cutting and making good the	no	5.00		
7	Supply, installation, testing and commissioning liquid soap dispenser with stainless steel lid and brackets fixed to wooden cleats with C.P. brass screws.	no	2.00		
8	Supply, installation, testing and commissioning of aluminium body compact Hand Dryer complete as per manufacturer specification. (Euronics EH	no	2.00		
	<b>Total Cost</b>				